



Terrazzo range available as tile and large slabs



CS-W1



CS-W5



CS-W6



CS-G3



CS-G2



CS-W7



CS-WV



CS-G4



CS-B2



CS-N2



CS-G5



CS-C4



CS-C2



CS-C5



CS-G6



CS-R2



CS-V3

3000x1250x 20, 30 and 40mm

600x600x20mm



- **STONE AND AGGLOMERATES**
- **MARBLE**
- **GRANITE**



WHAT IT'S FOR

- Protects and revives the original colour of polished, untreated and tumbled natural stone.
- Deeply penetrates the material and protects it from watery or oily stains and dirt.
- Ideal for all stone applications, worktops and any decorative stone objects.
- Excellent for use internally and externally.

ADVANTAGES

- Produces a reviving effect on all finishes.
- For indoor and outdoor use.
- Does not yellow, resists UV radiation, and it provides enduring protection.
- Extremely high coverage.
- Does not form surface film.
- The product is certified food-safe.

HOW TO USE IT

No dilution required: ready to use.

Application:

1. Apply **FILASTONE PLUS** on dry surfaces using a brush, sponge or other appropriate tool.
2. During application, rub the surface with a sponge or a cloth, so that the product penetrates and any excess can be removed.
3. The floor is ready for use after about eight hours.
4. To improve colour revival, apply several coats of the product within 8-hour intervals.

Maintenance: diluted solution of **FILACLEANER**.

FOR PROFESSIONAL USE ONLY:

spray the product (airless system) on vertical surfaces until they are saturated and use appropriate PPE, as indicated in the safety information sheet.

Caution:

Once treated with **FILASTONE PLUS**, the stone surface cannot be restored to its original condition: before treating the surface, carry out a spot test to verify the final colour effect. It is recommended, for external surfaces, to repeat the treatment every year so that the enhancing effect is assured. It does not protect marble and limestone from acid. Do not apply the product externally if rain is forecast.

COVERAGE

With one litre:

Polished stone	30/50 m ²
Unpolished stone	15/25 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

250-ml bottles in boxes of 12.

1-litre cans in boxes of 6.

5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

TEMPERATURES

Storage temperature: from 0°C to 30°C

The product should be applied to materials with temperature between 5° and 30°C.

COMPOSITION

A mixture of silicon compounds dispersed in de-aromatised hydrocarbon solvent.

LABELLING

Warning: Danger

Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations. Contains: NAPHTA (PETROL) HYDROTREATED HEAVY



TECHNICAL FEATURES

Appearance: transparent liquid

Colour: colourless

Odour: typical solvent smell

Density: 0,874 kg/l

Flashpoint: 40°C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.